

## Wall Lantern

 Wall mounted • Wet location listed **PROGRESS LED**


### Description:

Inspired by traditional lantern styles, Whitacre incorporates handsome details. Clear seeded glass surrounds an etched opal glass candle diffuser. An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.

### Specifications:

- Antique Bronze (-020) (painted)
- Aluminum construction
- Clear Seeded with Etched Ivory diffuser Glass globe
- Inspired by traditional lantern styles, Whitacre incorporates handsome details
- An Antique Bronze finish complements a variety of exteriors, including Transitional and Traditional and Farmhouse designs.
- Clear seeded glass surrounds an etched opal glass candle diffuser
- Includes one 17-watt replaceable LED modules Warm white, 3000K, color temperature, 90 CRI
- 1276 lumens, 73 lumens per watt (source)
- Wall lantern adds illumination to walkways and pathways to enhance safety and security
- Replaceable light engine is California JA8 certified
- Can also be used in interior settings and paired with decorative fixtures for creative design ideas.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

### Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1276/73 (LM-82)
Lumens/LPW (Delivered)	706/40.6 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30°C
Warranty	5 year limited warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 JA8-2016

## P560070-020-30

### Images:



### Dimensions:

Width: 12-3/8"  
Depth: 12"  
Height: 22"  
H/CTR: 4-3/4"

Glass  
Width: 7-7/8"  
Height: 12-5/8"  
Glass 2  
Width: 4-3/4"  
Length: 4-3/4"  
Height: 4-3/4"

**P560070-020-30****Dimming Notes:**

---

P560070 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Lutron Lumea LG-603PG

Leviton SureSlide 6672

Leviton SureSlide 6674

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Pass & Seymour Harmony DCL453PTCCCV6

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYL-600P

Lutron Maestro MA-600

Lutron NOVA T NTLV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.