

| Project:     |  |
|--------------|--|
| ixture Type: |  |
| ocation:     |  |
| Contact:     |  |

## One-Light Small LED Wall Lantern

Wall mounted • Wet location listed PROGRESS LED





### **Description:**

Northampton LED lanterns take a designer influenced approach for these updated outdoor wall lanterns. The distinctive styles provide a modern accent to your home with striking textured glass in a classic fluted pattern. A Black frame highlights clear fluted glass panels with a metallic silver interior reflector which creates a beautiful glow of light.

## **Specifications:**

- Black (-031) (painted)
- Aluminum construction
- Ribbed Clear Glass Panel, Ribbed Clear Glass Panel
- Northampton LED offers a designer-influenced outdoor wall lantern featuring visual interest
- Features clear ribbed glass panels with an intriguing decorative pattern
- 1-light small 9-watt LED wall lantern
- · Aluminum frame
- Measures 6 3/4" W x 12 1/2" H
- 324 lumens, 34.1 lumens per watt (delivered)
- Warm white 3000K lighting color and 90+CRI
- Part of Progress Lighting's Design Series designer-influenced collections that make a statement within the home
- · Ideal for Modern or Urban Industrial architectural exteriors
- Outdoor lanterns add illumination to exterior spaces such as patios or porches to enhance safety and security, while enhancing curb appeal
- Replaceable light engine is California JA8 certified
- Wet location listed
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- Mounting plate for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

## Performance:

| Number of Modules      | 1                                   |
|------------------------|-------------------------------------|
| Input Power            | 9w                                  |
| Input Voltage          | 120 V                               |
| Input Frequency        | 60 Hz                               |
| Lumens/LPW (Source)    | 624/66 (LM-82)                      |
| Lumens/LPW (Delivered) | 324/34.1 (LM-79)                    |
| ССТ                    | 3000 K                              |
| CRI                    | 90 CRI                              |
| Life (hours)           | (L70/TM-21)                         |
| FCC                    | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp        | -30 ℃                               |
| Warranty               | 5 year limited warranty             |
| Labels                 | cCSAus Wet location listed          |
|                        | ENERGY STAR® qualified              |
|                        | Meets California Title 24 JA8-2016  |
|                        |                                     |

## P560108-031-30

#### Images:



#### **Dimensions:**

Width: 6-3/4" Depth: 5" Height: 12-1/2" H/CTR: 6-1/4"

Glass Width: 2-7/8" Length: 0-1/8" Height: 9-3/4" Glass 2 Width: 2-7/8" Height: 9-3/4"



# One-Light Small LED Wall Lantern





P560108-031-30

#### **Dimming Notes:**

P560108 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Leviton SureSlide 6672

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.