

Project:			
Fixture Type:			
Location:			
Contact:			

One-Light Wall Sconce

Wall mounted • Damp location listed PROGRESS LED





Description:

Inspired by beautiful glass forms commonly found in a science lab, Beaker has a heightened sense of modern industrial styling. The 9W LED source offers energy efficient and cost savings benefits, while the industrial-inspired design complements a variety of mid-century modern interior designs. The one-light wall sconce has half clear, half mirrored glass with a Polished Chrome frame.

Specifications:

- Polished Chrome (-15) (plated)
- Steel Construction
- Mirror/Clear glass cylinder, White acrylic Diffuser
- LED Module is replaceable (part # 93054049)
- · Inspired by beautiful glass forms commonly found in a science lab.
- · Heightened sense of modern industrial styling.
- · Vessels are suspended from herringbone cloth cords.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 36" of wire supplied
- · ENERGY STAR® qualified

Performance:

Number of Modules	1		
Input Power	9w		
Input Voltage	120 V		
Input Frequency	60 Hz		
Lumens/LPW (Source)	623/69.2 (LM-82)		
Lumens/LPW (Delivered)	316.3/43.3 (LM-79)		
CCT	3000 K		
CRI	90+		
Life (hours)	60,000 (L70/TM-21)		
FCC	Meets FCC Title 47, Part 15 Class B		
Min. Start Temp	-30 °C		
Max. Operating Temp	30 °C		
Warranty	5 year warranty		
Labels	cCSAus Damp location listed		
	ENERGY STAR® qualified		

P7117-1530K9

Images:



Dimensions:

Width: 4-3/4" Depth: 9-1/8" Height: 17" H/CTR: 4"

Glass Width: 3-15/16" Length: 3-15/16" Height: 925" Glass 2

Width: 2-15/16" Length: 2-15/16" Height: 0-11/16"



One-Light Wall Sconce

Wall mounted • Damp location listed PROGRESS LED



P7117-1530K9

Dimming Notes:

P7117 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.